

Albury Consolidated Industries (T/A **WiseLiving**) A.B.N 34 087 962 338 A.C.N 087 962 338 PO Box 565 Albury 2640 | 89 North St Albury NSW 2640 Ph +61 2 6021 2200 | Fax +61 2 60 21 33 01 email - info@wiseliving.com.au

amdel report

AS 2918: 1990

SUPREME MKIII

CONFORMANCE CRITERIA

Client:Thermalux Stoves Pty LtdReport Date:M4145/92Client Ref:Request by P. CannonDate:20/8/1991

Test Specification: Australian Standard 2918:1990, Appendix B

Test Fuel: Wood & Coal briquettes **Test Date:** 15/8/1991

Appliance Model: Thermalux Supreme Mk 3 Solid Fuel Cooker (with domestic hot water booster)

Manufactured for: Thermalux Stoves Pty Ltd

Flue System: Standard Flue Kit as per 2918:1990 (A default decorative mesh flue kit – the mesh must have a

solid back)

The 150mm diameter flue pipe was encased in a 200mm diameter steel casing from the stove top to the ceiling drop box (venting into the drop box). A 200mm long 120° circumference flue shield was


attached to bottom end of the casing.

<u>Hearth:</u> 18mm thick sheet of fibre-cement with a 25mm ventilated air gap underneath.

<u>Test Installation:</u> The appliance was connected to the hot water circuit. It was installed with a rear wall

clearance of 75mm, a left hand side wall clearance of 50mm below the hot plate and 600mm above the hot plate, and a right hand side wall clearance of 100mm below the hot plate and

700mm above the hot plate.



<u>Conclusion:</u> When installed as described above, the appliance tested complied with the requirements of AS

2918:1990.

William V Yeo Manager Material Services Approved Signatory Michael J Greenwood Product Testing Officer Laboratory Registration No. 2326

This laboratory is registered by the National Association of Testing authorities Australia. The test(s) reported herein have been performed in accordance with its terms of registration. This document shall not be reproduced except in full.